

THE COCKROACH TERMINADOR MASTER PLUS 2000

Cockroaches are media of many diseases, and are serious indoor insect pest! Cockroaches have many different species but generally have similar habits, and love to live in warm, humid, and dark environment, such as kitchen, storage room, bathroom, bedroom, sewer, septic tank, etc. Cockroaches are tenacious of life and multiply rapidly, and have been survived on the earth for 400 million years. They eat anything, including wood, clothes, paper, and rubbish. They are good at crawling to easily move in very narrow spaces without being retarded by any indoor furnishings, WE PROVIDE THE SOLUTION FOR

Contact: manager@solartechsystems.com

www.solartechsystems.com



ATLANTS's team has been manufacturing electronic pest killers and repellers since +15 years ago. We will contantly strive to be the leaders in the world in advancements. By using most advances technologies, atlants provides the most complete and powerful protection available on the market today. Advanced Intelligent technology . With ATLANTS Pest control has never been so advanced and so simple.

The **MASTER PLUS 2000** can be used anywhere , can be used connected to electric network or by AA size batteries.

**NO TOXICS / NO CHEMICALS / ECOLOGIC
SAFE , CLEAN AND EFFECTIVE
SILENT OPERATION
UP TO 10 YEARS OF CONTINUAL OPERATION.
REMOVABLE COVER FOR EASY CLEANING.
COST PENNIES A MONTH TO OPERATE.**

**SUPERIOR TO ANY OTHER SYSTEM FOR KILLING
COCKROACHES AVAILABLE IN THE MARKET**



**KILL INDEED ALL
TYPE OF
COCKROACHES**

**Ideal in kitchens, restaurants,
homes, hotels, food preparing or
storing areas.....**

Technical specifications:

Input: 9V DC, supplied by 6 pieces of size AA. batteries , or using a AC adaptor of 110V or 220-240V/60Hz/9V/ 200mA.

Operation mode:

Kill cockroaches by electric inner system with electronic control using cyclic discharge , Also manual discharge available by pressing and hold the power button to achieve continuous forced discharges

Power Consumption: 0.1W on average by static timing; or an instantaneous power consumption less than 2W on average by dynamic discharge.

Frequency: 20 KHz \pm 10%.

Voltage: Pulse wave, peak-to-peak voltage of 4.5KV \pm 20% (resistive load of 100K Ω).

Safety Protection: Micro switch, disconnected as soon as the box is opened.

Dimensions: 220mm x 160mm x 65mm

Box Material: ABS strong and durable.

Electric Shock Plate: Stainless steel SUS304. Weight: 345mg.

Effective area: About 27 square meters . It is required 1 unit per floor or room

ATLANTS

**RÖHS CE
COMPLIANT**

Contact: manager@solartechsystems.com

www.solartechsystems.com